

# Control System

CONTROL SYSTEM

# ROXEL

CE 0197 FC RoHS



## DC1800



- One channel can control 20 unit receivers at most
- Power: 3V 1 unit battery CR2450; Battery usage life: > 1 years
- Transmit Distance: outdoor > 100 meters, indoor > 35 meters.
- Transmit Frequency: 433.92MHz±100KHz
- Transmit Power: 10mW
- Outside dimension: 130×44×10.5mm

## Portable single-channel wall-mounted emitter DC1850



- You can mount it to any desired position without wiring.
- One emitter can control 1 group receivers separately, each group can control 20 unit receivers at most
- Power: 3V 1 unit battery CR2430; Battery usage life: > 1 years
- Transmit Distance: outdoor > 100 meters, indoor > 35 meters.
- Transmit Frequency: 433.92MHz±100KHz
- Transmit Power: 10mW
- Outside dimension: 86×86×11.7mm

## 15-channel LCD control emitter DC1802



- With group control function
- One emitter can control 15 group receivers separately, each group can control 20 unit receivers at most
- Power: 3V 1 unit battery CR2450; Battery usage life: > 1 years
- Transmit Distance: outdoor > 100 meters, indoor > 35 meters.
- Transmit Frequency: 433.92MHz±100KHz
- Transmit Power: 10mW
- Outside dimension: 130×44×10.5mm

## Portable single-channel time emitter DC1855



- Time display function
- Timing switch function
- You can mount it to any desired position without wiring.
- One emitter can control 1 group receivers separately, each group can control 20 unit receivers at most
- Power: 3V 1 unit battery CR2430; Battery usage life: > 1 years
- Transmit Distance: outdoor > 100 meters, indoor > 35 meters.
- Transmit Frequency: 433.92MHz±100KHz
- Transmit Power: 10mW
- Outside dimension: 86×86×11.7mm

## Portable 5-channel time emitter DC1856



- Time display function
- Timing switch function
- You can mount it to any desired position without wiring.
- One emitter can control 1 group receivers separately, each group can control 20 unit receivers at most
- Power: 3V 1 unit battery CR2430; Battery usage life: > 1 years
- Transmit Distance: outdoor > 100 meters, indoor > 35 meters.
- Transmit Frequency: 433.92MHz±100KHz
- Transmit Power: 10mW
- Outside dimension: 86×86×11.7mm